

[English](#) | [Deutsch](#) [Log in](#) or [Sign up](#)[Tutorials](#)[Tags](#)[Forums](#)[Contribute](#)[Subscribe](#)[ISPConfig](#)[News](#)[Tutorials](#)[How To Create A Local Debian/Ubuntu Mirror Wi...](#)[Sign up now!](#)

How To Create A Local

On this page

- [How To Create A Local Debian/Ubuntu Mirror With apt-mirror](#)
 - [1 Preliminary Note](#)
 - [2 Install apt-mirror](#)
 - [2.1 Modify /etc/apt/sources.list \(Debian Sarge only\)](#)
 - [2.2 Install apt-mirror](#)
 - [3 Install Apache](#)
 - [4 Configure apt-mirror](#)

Debian/Ubuntu Mirror With apt-mirror

Version 1.0

Author: Falko Timme

This tutorial shows how to create a Debian/Ubuntu mirror for your local network with



Tutorial Info

Author:

falko

Tags:

debian, ubuntu

VMware image download

Local Debian / Ubuntu Mirror (without repositories - run "su - apt-mirror -c apt-mirror" to download them)

Download:
Local_Debian_Ubuntu_Mirror_With_apt-mirror.zip

Guide: VMWare Image Import Guide.

Other Downloads: List of all VMWare Images

Download

Share This Page

Tweet

Recommend 28

G+1 3

the tool apt-mirror. Having a local Debian/Ubuntu mirror is good if you have to install multiple systems in your local network because then all needed packages can be downloaded over the fast LAN connection, thus saving your internet bandwidth.

I want to say first that this is not the only way of setting up such a system. There are many ways of achieving this goal but this is the way I take. I do not issue any guarantee that this will work for you!

1 Preliminary Note

You can set up a Debian and Ubuntu mirror on both Debian and Ubuntu systems, i.e., a Debian system can be a Debian **and** a Ubuntu mirror, as well as a Ubuntu system can be a Ubuntu **and** a Debian mirror.

Please note that you need a fast internet connection to download all the packages to your mirror as well as a lot of hard disk space. In my tests I mirrored the main, contrib, and non-free sections of Debian Sarge and the main, restricted, and universe sections of Ubuntu Edgy Eft which took about 25GB of hard disk space and about 6 hours of download time on a 16MBit DSL line.

I will not mirror security updates in this tutorial - I think it's a good idea to always download security updates directly from the internet. That way you can be sure you get the latest ones.

I've tested this on a Debian Sarge and a Ubuntu Edgy Eft system. If you use different Debian/Ubuntu versions, the procedure might differ a little bit. You should have already set up a basic Debian Sarge system (e.g. as outlined on pages one and two of http://www.howtoforge.com/perfect_setup_debian_sarge) or a basic Ubuntu Edgy Eft system (e.g. as outlined on pages one to three of http://www.howtoforge.com/perfect_setup_ubuntu_6.10).

In this example my local mirror has the IP address *192.168.0.100*.

2 Install apt-mirror

2.1 Modify `/etc/apt/sources.list` (Debian Sarge only)

If you are on Debian Sarge, you must modify `/etc/apt/sources.list` to install apt-mirror. I don't know if this is necessary on Debian Etch or Sid, please try it

yourself. This step is not necessary for Ubuntu Edgy Eft.

```
vi /etc/apt/sources.list
```

Please add the following line to the file:

```
[...]
deb http://apt-mirror.sourceforge.net/ apt-mirror/
[...]
```

Then update the packages database:

```
apt-get update
```

2.2 Install apt-mirror

This step is for all systems (Debian and Ubuntu). To install apt-mirror, please run

```
apt-get install apt-mirror
```

3 Install Apache

Later on, I want to access my new local Debian/Ubuntu mirror over http, therefore I install the Apache web server now:

```
apt-get install apache2
```

The default document root is `/var/www`, I will create symlinks from that directory to the location of the Debian and Ubuntu repository later on.

4 Configure apt-mirror

apt-mirror's configuration file is `/etc/apt/mirror.list`. There should already be a default configuration in it; on Debian Sarge the file looks like this:

```
# apt-mirror configuration file

##
## The default configuration options (uncomment and change to override)
##
#
# set base_path          /var/spool/apt-mirror
# set mirror_path        $base_path/mirror
# set skel_path           $base_path/skel
# set var_path           $base_path/var
#
# set defaultarch
# set nthreads           20
#

##
## Example sources
##
```

```
# sarge's section
deb http://ftp.fi.debian.org/debian sarge main contrib
non-free
deb-src http://ftp.fi.debian.org/debian sarge main contrib
non-free

deb http://security.debian.org/debian-security sarge/updates
main contrib non-free
deb-src http://security.debian.org/debian-security sarge/updates
main contrib non-free

deb http://ftp.fi.debian.org/debian sarge main/debian-installer

# sarge-proposed-updates's section
deb http://ftp.fi.debian.org/debian sarge-proposed-updates
main contrib non-free
deb-src http://ftp.fi.debian.org/debian sarge-proposed-updates
main contrib non-free

# sid's section
deb http://ftp.fi.debian.org/debian sid main contrib non-free
deb-src http://ftp.fi.debian.org/debian sid main contrib
non-free

deb http://ftp.fi.debian.org/debian sid main/debian-installer

# experimental section
deb http://ftp.fi.debian.org/debian ../project/experimental
main contrib non-free
deb-src http://ftp.fi.debian.org/debian ../project/expe
```

```
rimental main contrib non-free

##
## Cleaner configuration example
##
#
# set cleanscript $var_path/clean.sh
#

# Cleaning section
clean http://security.debian.org/
clean http://ftp.fi.debian.org/

skip-clean http://ftp.fi.debian.org/doc/
skip-clean http://ftp.fi.debian.org/tools/
skip-clean http://ftp.fi.debian.org/debian-cd/
skip-clean http://ftp.fi.debian.org/debian-minicd/
skip-clean http://ftp.fi.debian.org/debian/dists/sarge/
main/installer-i386/
skip-clean http://ftp.fi.debian.org/debian/dists/sid/main/
installer-i386/
skip-clean http://ftp.fi.debian.org/debian/doc/
skip-clean http://ftp.fi.debian.org/debian/tools/
skip-clean http://ftp.fi.debian.org/debian/project/
skip-clean http://ftp.fi.debian.org/debian-non-US/project/
```

On Ubuntu Edgy Eft, the file looks like this:

```
##### config #####
#
# set base_path    /var/spool/apt-mirror
#
```

```
# if you change the base path you must create the direc
tories below with write privlages
#
# set mirror_path  $base_path/mirror
# set skel_path    $base_path/skel
# set var_path     $base_path/var
# set cleanscript $var_path/clean.sh
# set defaultarch
set nthreads      20
set tilde 0
#
##### end config #####

deb http://archive.ubuntu.com/ubuntu edgy main restrict
ed universe multiverse
deb http://archive.ubuntu.com/ubuntu edgy-updates main
restricted universe multiverse
#deb http://archive.ubuntu.com/ubuntu edgy-backports ma
in restricted universe multiverse
deb http://archive.ubuntu.com/ubuntu edgy-security main
restricted universe multiverse
#deb http://archive.ubuntu.com/ubuntu edgy-proposed mai
n restricted universe multiverse

deb-src http://archive.ubuntu.com/ubuntu edgy main rest
ricted universe multiverse
deb-src http://archive.ubuntu.com/ubuntu edgy-updates m
ain restricted universe multiverse
#deb-src http://archive.ubuntu.com/ubuntu edgy-backport
s main restricted universe multiverse
deb-src http://archive.ubuntu.com/ubuntu edgy-security
main restricted universe multiverse
#deb-src http://archive.ubuntu.com/ubuntu edgy-proposed
main restricted universe multiverse

clean http://archive.ubuntu.com/ubuntu
```


If you compare the file with `/etc/apt/sources.list`, you will see that it's very similar. `/etc/apt/mirror.list` mainly lists the repositories that should be mirrored, plus a few other options.

Now we modify `/etc/apt/mirror.list`. As I said before, I want to mirror the main, contrib, and non-free sections of Debian Sarge and the main, restricted, and universe sections of Ubuntu Edgy Eft, but I don't want to mirror the security updates as these should be downloaded directly from the internet. Also, I don't want to mirror the source packages because in 95% of all installations you don't need source packages, and they need a lot of space on the hard disk. So my `/etc/apt/mirror.list` looks like this:

```
vi /etc/apt/mirror.list
```

```
# apt-mirror configuration file

##
## The default configuration options (uncomment and change to override)
##
#
# set base_path      /var/spool/apt-mirror
# set mirror_path    $base_path/mirror
# set skel_path      $base_path/skel
# set var_path       $base_path/var
#
# set defaulttarch
# set nthreads       20
#

##
## Example sources
##
```

```
# sarge's section
deb http://ftp.de.debian.org/debian sarge main contrib
non-free

# Ubuntu Edgy Eft
deb http://de.archive.ubuntu.com/ubuntu/ edgy main rest
ricted universe

##
## Cleaner configuration example
##
#
# set cleanscript $var_path/clean.sh
#

# Cleaning section
clean http://ftp.de.debian.org/
clean http://de.archive.ubuntu.com/
```

Please note that I used *ftp.de.debian.org* instead of *ftp.fi.debian.org* and *de.archive.ubuntu.com* instead of *archive.ubuntu.com*. You should use mirrors that are close to you, so if you are in the U.S., for example, replace *de* with *us*, and so on.

The cleaning section at the end tells apt-mirror in which directories on the local hard disk it should check to see if hard disk space can be freed. I want to check the whole local repositories for both Debian and Ubuntu, therefore I specify

```
clean http://ftp.de.debian.org/
clean http://de.archive.ubuntu.com/
```

If you want to use other Debian/Ubuntu versions, simply replace *sarge* with *etch* or *sid* and *edgy* with *breezy*, *dapper*, etc.

Next >>

 [view as pdf](#) |  [print](#)

Share this page:

Tweet

Follow @howtoforgecom

10.4K followers

Recommend

1

 3

Sub pages

How To Create A Local Debian/Ubuntu Mirror With apt-mirror

How To Create A Local Debian/Ubuntu Mirror With apt-mirror - Page 2

How To Create A Local Debian/Ubuntu Mirror With apt-mirror - Page 3

3 Comment(s)

Add comment

Name *

Email *

  **B** *I* 

p

I'm not a robot

reCAPTCHA
Privacy - Terms

Submit comment

Comments

From:

Reply

If you have both 32bit (i386) and 64 bit (amd64) you can have apt-mirror get the packages for both architectures. Just add the architecture after deb on each line.

Example:

```
deb-amd64 http://ftp.osuosl.org/pub/ubuntu gutsy main restricted universe multiverse
```

```
deb-i386 http://ftp.osuosl.org/pub/ubuntu gutsy main restricted universe multiverse
```

From: Anonymous

Reply

Thanks for the info. We just create a repo.

Thanks,
Ivu Loto Team

From: TCPMeta

Reply

I followed your guide to the T for the mirror portion. I am also using the mirror as a PXE

server to load the debian install image. My clients do not like the mirror. I select HTTP and point it to my server's IP 192.168.1.100, point it to /debian/ and it asks what version I want and after I select Wheezy it fails. Might give it a shot with FTP next.

Tutorials

How To Create A Local Debian/Ubuntu Mirror Wi...

Xenforo skin by Xenfocus

Howtoforge © projektfarm GmbH.

[Contact](#)

[Help](#)

[Imprint](#)

[Tutorials](#)

[Top](#)



[Terms](#)